



U.S. Department of Labor  
Occupational Safety and Health Administration  
(Non-Mandatory Form). Format meets ANSI Z400.1-  
1998, OSHA 1910.1200 and WHMIS requirements.

# Safety Data Sheet

"According to (EC) No. 1907/2006 REACH"

---

## Section 1: Product and Company Identification

---

Product Name:	<b>E7024</b>
Product type and use:	Rutile type electrode which has high welding efficiency and resistance to high current. Cost saving in groove welding and in flat fillet welding.
Classification:	AWS A5.1: E 7024
Manufacturer:	TECHNIWELD USA LLC.
Physical Address:	6205 BOAT ROCK BLVD ATLANTA, GA 30336
Mailing Address:	P.O. Box 44226 ATLANTA, GA 30336
Business Phone:	404-699-9900
Business Fax:	404-699-7800
E-mail Address:	info@TECHNIWELDUSA.COM
Web Address:	www.TECHNIWELDUSA.COM
Emergency Phone:	CHEMTREC (24-Hour) 1-800-424-9300 Outside of the USA & Canada 1-703-527-3887
Date of Preparation:	June 2, 2015 (Revised June 23, 2015)

---

## Section 2: Hazard(s) Identification

---

The products are not considered to be hazardous by the manufacturer; however they can contain hazardous ingredients. Different kinds of fume and dust occur during the welding and grinding processes. Chromium-VI compounds and nickel oxides might occur if product contains nickel and chromium, which are classified as carcinogenic. In addition irritant substances such as fluorides and manganese oxides as well as fine dusts (mostly iron oxides) occur.

Welding electrodes and wires are non-hazardous solids at ambient temperature. Skin contact is normally not hazardous but should be avoided to prevent possible allergic reaction. Avoid eye contact or inhalation of dust or fumes from the product. Occupational exposure limits of components are described in section 8. Actual exposure should be determined by monitoring the fume in the operator's breathing zone.

When this product is used in a welding process the most significant hazards are electric shock, fumes, gases, radiation, spatter, slag and heat. Electric shock can kill. Arc rays can damage eyes and burn skin. Spatter and slag can damage eyes. Spatter, slag, melting metal, arc rays and hot welds can cause burn injuries and start fires. When welding arc or torch flame may be a source of ignition of combustible.

The primary entry route for welding fumes and gases is by inhalation. Short term overexposure to welding fumes may result in symptoms like dizziness, nausea, dryness or irritation of the nose, throat or eyes and may aggravate pre-existing respiratory problems (e.g. asthma, emphysema). Long term overexposure to welding fumes may affect pulmonary function. Prolonged inhalation of nickel and chromium compounds above safe exposure limits can cause cancer. Overexposure to

manganese and manganese compounds above safe exposure limits can cause irreversible damage to the central nervous system, including the brain, symptoms of which may include slurred speech, lethargy, tremor, muscular weakness, psychological disturbances and spastic gait.

Welding fumes and gases cannot be classified simply. The composition and quantity of both are dependent upon the metal being welded, the process, procedure and electrodes used. Other conditions which also influence the composition and quantity of the fumes and gases to which workers may be exposed include ; coatings on the metal being welded ( such as paint, plating, or galvanizing ), the number of welders and the volume of the work area, the quality and amount of ventilation, the position of the welders head with respect to the fume plume, as well as the presence of contaminants in the atmosphere ( such as chlorinated hydrocarbon vapors from cleaning and degreasing activities ). When the electrode is consumed, the fume and gas decomposition products generated are different in percent and form from the ingredients listed in Section 3. Most fume ingredients are present as complex oxides and compounds and not as pure metals. Decomposition products of normal operation include those originating from the volatilization, reaction, or oxidation of the materials shown in Section 3, plus those from the base metal and coating, etc. as noted above.

Welding fumes must be considered as carcinogens. The International Agency for Research on Cancer has classified welding fumes as possibly carcinogenic to humans (Group 2B). Hence, before using welding wire and/or electrodes read and understand the manufacturer's instructions, SDSs, and your employer's safety practices. Take necessary precautions and use proper ventilation and absorption system to remove fumes and gases from your breathing zone and the general area. Keep your head out of the fumes. Do not breathe gas and fumes. Besides, wear correct eye, ear, and body protection and do not touch live electrical parts.

---

### Section 3: Composition and Information on Ingredients

---

INGREDIENT	CAS NO.	%WEIGHT	Classification according to Regulation (EC) No 1272/2008 [CLP]	Classification according to 67/548/EEC, Dangerous Substances Directives
CARBON	7440-44-0	< 0.1	-	-
IRON	7439-89-6	Bal.	-	-
MANGANESE	7439-96-5	< 4	-	-
ALUMINIUM OXIDE	1344-28-1	< 5	-	-
CELLULOSE	9004-34-6	< 3	-	-
MICA	12001-26-2	< 5	-	-
CALCIUM CARBONATE	1317-65-3	< 3	-	-
TITANIUM DIOXIDE	13463-67-7	< 10	-	-
RUTIL (TiO <sub>2</sub> )	1317-80-2	< 10	-	-
QUARTZ	14808-60-7	< 5	-	-
SILICIC ACID, POTASSIUM SALT	1312-76-1	< 10	-	-

\* During use manganese dioxide may occur

---

### Section 4: First Aid Measures

---

- Inhalation:** If dust or fumes inhaled, provide fresh air and call physician. If breathing has stopped, perform artificial respiration and obtain medical assistance immediately.
- Eye contact:** For radiation burns due to arc flash, see physician. To remove dust, fumes or particulates flush with water for at least fifteen minutes. If irritation persists, obtain medical assistance.
- Skin contact:** The unused welding product does not irritate the skin but wear gloves to prevent possible allergic reactions. For skin burns from arc radiation, promptly flush with cold water. Get medical attention for burns or irritations that persist. To remove dust or particles wash with mild soap and water.

**Electric shock:** Disconnect and turn off the power. Use a nonconductive material to pull victim away from contact with live parts or wires. If not breathing, begin artificial respiration, preferably mouth-to-mouth. If no detectable pulse, begin Cardio Pulmonary Resuscitation (CPR). Immediately call a physician.

**General:** Move to fresh air and call for medical aid.

---

## Section 5: Fire Fighting Measures

---

Welding consumables applicable to this sheet as shipped are non reactive, non-flammable, non-explosive and essentially nonhazardous until welded. Welding arcs and sparks can ignite combustibles and flammable products. Unused welding consumables may remain hot for a period of time after completion of welding process. Wear self-contained breathing apparatus as fumes or vapours may be harmful. See American National Standard (ANSI) Z49.1 for further general safety information on the use and handling of welding consumables and associated procedures.

---

## Section 6: Accidental Release Measures

---

Procedure for cleanup of spills or leaks: Not applicable. Solid objects can be picked up and placed into a container. Do not allow to enter surface, sewers or ground water. Wear proper personal protective equipment while handling.

---

## Section 7: Handling and Storage

---

**Handling:** Handle with care to avoid stings and cuts. Hold the welding wire manually when loosening the wire. Wear gloves when handling welding consumables. Wash hands / shower before breaks and end of work. Avoid exposure to dust. Local exhaust ventilation of the working area. Some individuals can develop an allergic reaction to certain materials. Retain all warning and identity labels.

**Storage:** Keep separate from chemical substances like acids and strong bases, which could cause chemical reactions. Avoid humidity and temperature shocks. Store welding consumables inside a room without humidity. Do not store welding consumables directly on the ground or beside a wall. Storage temperature  $21^{\circ}\text{C} \pm 2^{\circ}\text{C}$ , Relative humidity max. % 60. Because of any reason if protective nylon of the packing was torn or pierced and it won't be used, immediately the packing should be repacked.

---

## Section 8: Exposure Controls / Personal Protection

---

INGREDIENT	CAS NO.	EINECS NO.	OSHA EPL	ACGIH TLV 8-hour TWA
CARBON	7440-44-0 (1333-86-4 carbon black)	231-153-3	3.5 (as carbon black)	3.5 (as carbon black)
IRON + (as iron oxide)	7439-89-6	231-096-4	10	5 *
MANGANESE#	7439-96-5	231-105-1	5** (Fume) 3 STEL ***	0.2* 0.1 mg/m <sup>3</sup> (IHL) (for elemental and inorganic compounds)
SILICON+	7440-21-3	231-130-8	15 (total dust)-5*	-
ALUMINUM OXIDE##	1344-28-1	215-691-6	-	1 *
CALCIUM CARBONATE	1317-65-3	215-279-6	15 (total dust)-5* 5 (as CaO)	5 2 (as CaO)
TITANIUM DIOXIDE	13463-67-7	236-675-5	15 (total dust)	10 {A4}
SODIUM SILICATE	15859-24-2	239-981-7	N.A.	N.A.
SILICIC ACID, POTASSIUM SALT	1312-76-1	215-199-1	N.A.	N.A.

MICA	12001-26-2	None	3 *	3 *
CELLULOSE	9004-34-6	232-674-9	5 *	10

\*-Respirable Fraction- IHL- inhalable - \*\*-Ceiling Limit \*\*\*- Short Term. Exposure Limit # -Reportable material under Section 313 of SARA ## - Reportable material under SARA 313 only in fibrous form. + -As a nuisance particulate covered under " Particulates Not Otherwise Regulated" by OSHA or "Particulates Not Otherwise Classified" by ACGIH. {A1} -Confirmed Human Carcinogen per ACGIH.

{A4} - Not Classifiable as a Human Carcinogen per ACGIH. {A5} -Not Suspected as a Human Carcinogen per ACGIH 1999 ACGIH listed under Notice of Intended Changes. Limits of 10 mg/m<sup>3</sup> (inhalable fraction) and 3 mg/m<sup>3</sup> (respirable fraction) for elemental/metal and insoluble compounds and 0.5 mg/m<sup>3</sup> (respirable fraction) for soluble compounds are proposed and should be considered as trial limits. A3 - "Confirmed Animal Carcinogen"

1999 ACGIH listed under Notice of Intended Changes. A2 - "Suspected Human Carcinogen" Limits of 0.05 mg/m<sup>3</sup> (respirable fraction) are proposed and should be considered as trial limits.

The exposure limit for welding fume has been established at 5 mg/m<sup>3</sup> with OSHA's PEL and ACGIH's TLV. The Individual complex compounds within the fume may have lower exposure limits than the general welding fume PEL/TLV. An Industrial Hygienist, the OSHA permissible exposure Limits For Air Contaminants ( 29 CFR 1910-1000 ) and the ACGIH Threshold Limit Values should be consulted to determine the specific fume constituents present and their respective exposure limits.

VENTILATION: Use enough ventilation, local exhaust at the arc, or both to keep the fumes and gases below PEL/TLV's in the worker's breathing zone and the general area. Train the welder to keep his head out of the fumes. Keep exposures as low as possible.	
RESPIRATORY PROTECTION: Use NIOSH approved or equivalent fume respirator or air supplied respirator when welding in confined space or where local exhaust or ventilation does not keep exposure below the recommended exposure limit.	
HAND PROTECTION: Wear heat protecting gloves (Non-flammable). For hygiene wash hands before breaks and end of work.	
EYE PROTECTION: Wear helmet or use face shield with filter lens. As a rule of thumb begin with Shade Number 14. Adjust if needed by selecting the next lighter and/or darker shade number. Provide protective screens and flash goggles, if necessary, to shield others.	
PROTECTIVE CLOTHING: Wear hand, head and body protection which help to prevent injury from radiation, sparks and electrical shock. See Z49.1. At a minimum this includes welder's gloves and a protective face shield, and may include arm protectors, aprons, hats, shoulder protection, as well as dark nonsynthetic clothing. Train the welder not to touch live electrical parts and to insulate himself from work and ground.	
SPECIAL PRECAUTIONS (IMPORTANT): Maintain exposure below the PEL/TLV. Use industrial hygiene monitoring to ensure that your use of this material does not create exposures which exceed PEL/TLV. Always use exhaust ventilation. For hygiene, wash hands before breaks and end of work. Do not eat, drink or smoke in working areas.	

## Section 9: Physical and Chemical Properties

<b>Appearance:</b>	Solid, non-volatile.
<b>Colour:</b>	Varying color
<b>Odour:</b>	N/A
<b>Solubility in Water:</b>	Insoluble
<b>Self-igniting:</b>	N/A
<b>Danger of explosion:</b>	N/A

<b>Boiling Point:</b>	N/A
<b>Vapour Pressure(mm Hg.):</b>	N/A
<b>Vapour Density(air = 1):</b>	N/A
<b>Melting point:</b>	1300°C / >2300°F
<b>Density:</b>	N/A
<b>pH:</b>	N/A
<b>Evaporation Rate (Butyl Acetate =1):</b>	N/A
<b>Specific Gravity (H2O =1):</b>	N/A

---

## Section 10: Stability and Reactivity

---

**General:** These products are only intended for normal welding purposes.

**Stability:** These products are stable under normal conditions.

**Reactivity:** Contact with chemical substances like acids or strong bases could cause generation of gas.

Welding fumes and gases cannot be classified simply. The composition and quantity of both are dependent upon the metal being welded, the process, procedure and electrodes used. Other conditions which also influence the composition and quantity of the fumes and gases to which workers may be exposed include ; coatings on the metal being welded ( such as paint, plating, or galvanizing ), the number of welders and the volume of the work area, the quality and amount of ventilation, the position of the welders head with respect to the fume plume, as well as the presence of contaminants in the atmosphere ( such as chlorinated hydrocarbon vapors from cleaning and degreasing activities ). The amount of fume varies with the welding parameters. The concentration of a given fume or gas component may decrease or increase by many times the original concentration in the electrode/wire. Also, new compounds not in the electrodes/wire may form. Hence, welding fumes and gases cannot be classified simply. Most fume ingredients are present as complex oxides and compounds and not as pure metals. Decomposition products of normal operation include those originating from the volatilization, reaction, or oxidation of the materials shown in Section 3, plus those from the base metal and coating, etc. as noted above.

Reasonably expected gaseous products would include carbon oxides, nitrogen oxides and ozone. Air contaminants around the welding area can be affected by the welding process and influence the composition and quantity of fumes and gases produced.

Refer to applicable national exposure limits for fume compounds, including those exposure limits for fume compounds found in related section. Manganese also have low exposure limits, in some countries that may be easily exceeded.

---

## Section 11: Toxicological Information

---

### SHORT-TERM ( ACUTE ) OVEREXPOSURE EFFECTS:

WELDING FUMES - May result in discomfort such as dizziness nausea or dryness or irritation of nose, throat or eyes.

IRON, IRON OXIDE - None are known. Treat as nuisance dust or fume.

MANGANESE - Metal fume fever characterized by chills, fever, upset stomach, vomiting, irritation of the throat and aching of body. Recovery is generally complete within 48 hours of the overexposure.

ALUMINUM OXIDE - Irritation of the respiratory system

CALCIUM OXIDE – Dust or fumes may cause irritation of the respiratory system, skin and eyes.

MICA – Dust may cause irritation of the respiratory system, skin and eyes.

TITANIUM DIOXIDE – Irritation of respiratory system.

POTASSIUM OXIDE -Dust or fumes may cause irritation of the respiratory system, skin and eyes.

SILICA (AMORPHOUS) - Dust and fumes may cause irritation of the respiratory system, skin and eyes

**LONG-TERM ( CHRONIC ) OVEREXPOSURE EFFECTS:**

WELDING FUMES - Excess levels may cause bronchial asthma, lung fibrosis, pneumoconiosis or "siderosis".

IRON. IRON OXIDE FUMES - Can cause siderosis ( deposits of iron in lungs ) which some researchers believe may affect pulmonary function. Lungs will clear in time when exposure to iron and its compounds ceases. Iron and magnetite ( Fe<sub>3</sub>O<sub>4</sub> ) are not regarded as fibrogenic materials.

MANGANESE - Long-term overexposure to manganese compounds may affect the central nervous system. Symptoms may be similar to Parkinson's Disease and can include slowness, changes in handwriting, gait impairment, muscle spasms and cramps and less commonly, tremor and behavioral changes. Employees who are overexposed to manganese compounds should be seen by a physician for early detection of neurologic problems. Overexposure to manganese and manganese compounds above safe exposure limits can cause irreversible damage to the central nervous system, including the brain, symptoms of which may include slurred speech, lethargy, tremor, muscular weakness, psychological disturbances and spastic gait

CALCIUM OXIDE - Prolonged overexposure may cause ulceration of the skin and perforation of the nasal septum, dermatitis and pneumonia.

MICA – Prolonged overexposure may cause scarring of the lungs and pneumoconiosis characterized by cough, shortness of breath, weakness and weight loss.

ALUMINUM OXIDE - Pulmonary fibrosis and emphysema.

TITANIUM DIOXIDE - Pulmonary irritation and slight fibrosis.

POTASSIUM OXIDE -Prolonged overexposure may cause ulceration of the skin and perforation of the nasal septum, dermatitis and pneumonia.

SILICA (AMORPHOUS) - Research indicates that silica is present in welding fume in the amorphous form. Long term overexposure may cause pneumoconiosis. Noncrystalline forms of silica (amorphous silica) are considered to have little fibrotic potential.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** Persons with pre-existing impaired lung functions (asthma-like conditions). Persons with a pacemaker should not go near welding and cutting operations until they have consulted their doctor and obtained information from the manufacturer of the device. Respirators are to be worn only after being medically cleared by your company- designed physician.

**EMERGENCY AND FIRST AID PROCEDURES:** Call for medical aid techniques recommended by the American Red Cross. If irritation or flash burns develop after exposure, consult a physician.

---

**Section 12: Ecological Information**

---

Welding consumables and materials could degrade/weather into components originating from the consumables or from the materials used in the welding process. Avoid exposure to conditions that could lead to accumulation in soils or groundwater.

---

**Section 13: Disposal Considerations**

---

**WASTE DISPOSAL:** Disposal must be made according to official regulations. Discard any product, residue, disposable

container, or liner in an environmentally acceptable manner, in full compliance with Federal State and local regulations. Use recycling procedures for material if available.

---

## Section 14: Transportation Information

---

No international regulations or restrictions are applicable. No special precautions are necessary.

---

## Section 15: Regulatory Information

---

Welding electrodes/wires which are mentioned in this SDS do not require labelling under current chemical product classification and labelling regulations. Welding electrodes and wires are non-hazardous solids at ambient temperature. There is no risk of product phase. It may constitute risk during use!!!

Warning text on label:

ATTENTION!

Please read this label carefully. Protect yourself and others.

Take necessary precautions while welding. Obey working safety rules.

Use proper ventilation and absorption system to remove fumes and gases during welding.

Welding arc and hot welds can cause burn injuries and start fires.

Arc rays may injure your eyes and body. Use protector to eyes, body and ears.

Electrical shock can kill. Don't touch with naked hands to piece having electrical current.

Investigate working safety books relevant with this topic.

Read and understand the manufacturer's instructions and the precautionary label on the product.

Observe any federal and local regulations.

---

## Section 16: Other Information

---

In this publication, reference is made to the (EC) No. 1907/2006 REACH, Annex I of Directive 67/548/EEC and Directive 1999/45/EC, (EC) No. 1272/2008 [CLP] and American National Standard Z49.1, 'Safety in Welding and Cutting' published by the American Welding Society, P.O Box 051040. Miami, FL 33135 and OSHA Publication 2206 (29 CFR 1910) from the U.S. Government Printing Office, Washington, D.C. 2040. Copies are available from the indicated sources. Also, Suppliers' Safety Data Sheets on component is used for as reference.

This Safety Data Sheet has been revised due to new format. Contact TECHNIWELD at [www.Techniweldusa.com](http://www.Techniweldusa.com) or if you have questions about this SDS.

TECHNIWELD believes this data to be accurate and to reflect qualified expert opinion regarding research. However TECHNIWELD can not make any expressed or implied warranty as to this information.