



AG326050WTU

**32oz Tan Uncoated Heat Treated
Fiberglass Fabric**

Features

- High-temperature resistant tan uncoated fiberglass fabric.
- Chemical, oil, and corrosion resistant.
- Suitable for multiple welding, brazing, and soldering applications.
- May protect equipment from damage caused by sparks, heat, spatter, and more.
- Medium-high abrasion resistance.
- Temperature rating up to 1000°F

Technical Specifications

- **Weave:** Plain
- **Yarn:** **WARP:** ET9 860 tex; **WEFT:** ET9 1480 tex
- **Length:** 50 yds
- **Width:** 60"
- **Weight as per ASTM-D3776-2009:** 1088 g / m²
- **Ounces per Square Yard:** 32
- **Thickness as per ASTM-D1777-1996:** 1.7 mm
- **Thread count per cm as per ASTM-D3775-2008:** **WARP:** 6; **WEFT:** 3.6
- **Coating:** Uncoated, Heat Treatment, Tan
- **Total Weight as per ASTM-D3776-2009:** 1088 g / m²
- **Total Thickness as per ASTM-D1777-1996:** 1.7 mm
- **Tensile Strength as per ASTM-D5034-2001:** **WARP:** 2100 N/2.5 cm; **WEFT:** 1600 N/2.5 cm
- **Service Temperature:** 550 °C
- **Certifications:** Europe BSEN 476 part 7, European Union CE, America FM/ANSI 4950